

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
28 July 2005 (28.07.2005)

PCT

(10) International Publication Number
WO 2005/068154 A1

(51) International Patent Classification⁷: **B29C 45/16**,
45/14, B60R 13/02

(74) Agent: GUSTAFSON, Adam, M.; FOLEY & LARDNER
LLP, 777 East Wisconsin Avenue, Milwaukee, Wisconsin
53202-5306 (US).

(21) International Application Number:
PCT/US2005/000120

(22) International Filing Date: 3 January 2005 (03.01.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/534,314 3 January 2004 (03.01.2004) US

(71) Applicant (for all designated States except US): **JOHN-
SON CONTROLS TECHNOLOGY COMPANY**
[US/US]; 650 Waverly, Holland, Michigan 49423 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **SMITH, Nels, R.**
[US/US]; 10230 Springwood Drive, Holland, Michigan
49424 (US). **HANSEN, Scott, A.** [US/US]; 447 Pinewood
Court, Holland, Michigan 49424 (US). **STOUT, Jeffrey,
T.** [US/US]; 2050 Francis Avenue SE, Grand Rapids,
Michigan 49507 (US). **BUTZ, Andrew, R.** [US/US]; 2916
104th Avenue, Zeeland, Michigan 49464 (US). **FOX,
Bart, W.** [US/US]; 4654 Majestic Vue, Zeeland, Michigan
49464 (US).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.


(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,
SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN,
GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

[Continued on next page]

(54) Title: VEHICLE COMPONENT AND METHOD FOR MAKING A VEHICLE COMPONENT



(57) Abstract: A vehicle component and a method of making same is disclosed. The method comprises providing a flexible element (122), a shut-off member (26) movable between a first position and a second position, a first cavity defined when the shut-off member (26) is in the first position, a second cavity defined when the shut-off member (26) is in the second position; positioning the flexible element (122) within the first cavity or the second cavity; injecting a first resin (18) into the first cavity; moving the shut-off member (26) from the first position to the second position; and injecting a second resin (20) into the second cavity. The trim panel comprises a one-piece molded member having a first substrate portion made of the first resin (18), a second substrate portion made of the second resin (20), and a cushioned layer at least partially covering one of the first substrate portion and the second substrate portion.



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.